



LED available in red, green, blue or amber

The **NTDS24** Digital Clock syncs to any NTP (Network Time Protocol) source for accurate traceable time. The unit configures to time zone and Daylight Saving Time parameters and can be powered via PoE. WinDiscovery software is included.



## **Standard Features**

- 2.3 in (5.8 cm) 4-digit LED display
- LED available in red, green, blue or amber
- Syncs to any NTP or SNTP source for accurate and traceable time
- Retains time and date during loss of power and/or reference using a battery backed real-time clock (RTC) chip and maintenance-free rechargeable battery
- Configures to time zone and Daylight Saving Time
- WinDiscovery software utility included for easy configuration of clocks and generators within a network
- Fully configurable network settings, including DHCP / STATIC IP
- Configuration is saved to non-volatile memory and survives power losses
- Password protection prevents unauthorized tampering
- Display time in 12- or 24-hr format hh:mm
- Display date mm:dd
- Auto alternate between date and time display
- PM indicator
- Adjustable brightness levels with scheduled dimming
- Visibility: 100 feet (30 meters)

# **Options**

- Tilt-wall bracket
- Flush-mount bracket
- Stainless steel case
- Ceiling mount bracket

#### Pair with the RC1000 or RC600 to add count-up and count-down timer control functionality



#### 5-YEAR LIMITED PARTS & LABOR WARRANTY MADE IN THE USA

US/CAN: (800) 940-2248 INTL: +1 (636) 724-3666 sales@masterclock.com Masterclock.com

# Specifications

#### CONNECTORS

- Ethernet RJ45
- DC input
- USB for configuration

#### POWER

- Choice of PoE (IEEE802.3af) or DC (24 VDC)
- Power consumption < 8W

## **OPERATING PARAMETERS**

- Temperature: 0 to 60°C
- Humidity: Up to 90% (non-condensing)
- Storage Temperature: -40° to 185° F (-40° to 85°C)
- Storage Humidity: Up to 90% (non-condensing @ 25°C)

#### PHYSICAL

- Black powder-coated steel chassis
- IP Rating: IP40
- Size: 9.31w x 3.82h x 1.85d in (23.6w x 9.7h x 4.7d cm
- Weight: 2.0 lbs (0.9 kg)

## MTBF

86,700 - 100,000 hrs
All calculated using Fixed/Ground Mil HDBK 217F assumption

## COMPLIANCE

• FCC, ROHS, CE Marked, ANSI

