



FEATURES

- 15 character Dot Matrix Display
- 19" rack mount (STD 1RU 1 ¾")
- Configurable from Masterclock NTD series digital clock, as an auxiliary display
- Configurable from a PC serial port for use as a standalone alphanumeric display device
- RS232 serial interface or RS485 with up to 32 switch selectable addresses
- 1.2" (5.3cm) characters, 90 x 7 Red/Green LED matrix
- Red/Green/Amber monicolor modes
- Variable hue (red & green mix)
- Variable intensity
- Software and serial cable for RS232 provided
- Sample software and cable specification for RS485 downloadable from website

SPECIFICATIONS

Inputs

- RS485 serial communications (RJ12) up to 32 switch selectable addresses, with RJ12 pass thru
- RS232 serial communications (RJ12) with special serial cable

Power

- 93 – 263 VAC, 47 – 63 Hz
- IEC input connector
- AC power cords available at time of original order at no charge, available in US, UK, Euro & Aus/NZ standard plugs

Case

- 19" standard 1RU 1 ¾" rack mount case
- 5" depth
- Black anodized aluminum finish
- Available in off-white as special order

Operating Temperature and Humidity

- Temperature: 0 to +40°C
- Humidity: Up to 90% (non-condensing at +25°C)