



FEATURES

- 4" (10.2cm), 4 digit LED – display colors available in red, green, amber, and blue
- Syncs to external or internal NTP source for accurate traceable time
- Display time in 12 or 24 hr format – hh:mm
- Display date, or alternate between time and date
- Adjustable brightness levels
- All international time zones and automatic daylight saving times
- Wireless network available on special order
- Standard chassis colors are black or beige (off-white) powder coat
- Power-over-Ethernet or – worldwide AC Power
- CE marked for sale in EU – FCC, Class B, Emissions (pending)

SPECIFICATIONS

Setup and control software

- Supports DHCP/BOOTP for automatic acquisition of network address, nameservers, and time server configuration
- NTP synchronization options and more
- Provides dynamic configuration for networking parameters, time zone/daylight saving time
- Configure clocks through provided WinDiscovery software or TELNET
- WinDiscovery provides easy discovery and configuration of NTP clocks attached to the network without changing PC's network configuration
- Configuration is saved to non-volatile memory
- Encrypted network messages prevent unauthorized tampering of clock configuration

Physical

Size: 15.75w x 9.5h x 3.5d in
40w x 24h x 8.4d cm **Weight:** 8.6 lbs
3.9 kg

Connectors

- Ethernet – RJ45
- USB connector for setup (option)
- 2.1mm locking DC input jack (DC option)

Power

- Power consumption 15W
- PoE (to IEEE 802.3af standard) or
- AC option - International 115/230, 50/60 Hz
 - Supplied with your choice of US, Euro, British or AUS/NZ power cord – others available
- DC option
 - Includes external AC to DC wall-mount power supply with locking DC plug
 - International AC – 115/230, 50/60 Hz
 - Supplied with your choice of US, Euro, British or AUS/NZ plug – others available