






FEATURES

- 4" (10.2cm), 6 digit LED – display colors available in **red**, **green**, **amber**, and **blue**
- Syncs to external or internal NTP source for accurate traceable time
- Display time in 12 or 24 hr format – hh:mm:ss
- Display date - MM:dd:yy or dd:MM:yy or yy:MM:dd – configurable
- Adjustable brightness levels
- All international time zones and automatic daylight saving times
- Wireless network available on special order
- Standard chassis colors are black or beige (off-white) powder coat
- Power-over-Ethernet or worldwide AC Power
- CE marked for sale in EU – FCC, Class B, Emissions (pending)



2.3" Seconds Option

MOUNTING BRACKETS

| | |
|--|---|
| Wall Mount Bracket Included |  |
| Tilt Wall Bracket Option |  |
| Dual Face Ceiling Mount Option (see 3.7) | |
|  | |

SPECIFICATIONS

Setup and control software

- Supports DHCP/BOOTP for automatic acquisition of network address, nameservers, and time server configuration
- Provides dynamic configuration for networking parameters, time zone/daylight saving time
- Configure clocks through provided WinDiscovery software or TELNET
- WinDiscovery provides easy discovery and configuration of NTP clocks attached to the network without changing PC's network configuration
- Configuration is saved to non-volatile memory
- Encrypted network messages prevent unauthorized tampering of clock configuration

Physical

Powder-coated, non-rusting, welded steel chassis

Size: 25w x 6.8h x 2.1d in **Weight:** 7.6 lbs
 63.3w x 17.4h x 5.4d cm 3.5 kg

Connectors

- Ethernet – RJ45
- USB connector for setup (option)
- 2.1mm locking DC input jack (DC option)

Power

- Power consumption 15W
- PoE (to IEEE 802.3af standard) or
- DC option
 - Includes external AC to DC wall-mount power supply with locking DC plug
 - International AC – 115/230, 50/60 Hz
 - Supplied with your choice of US, Euro, British or AUS/NZ plug – others available

Operating Temperature and Humidity

- Temperature: 0 to +60°C
(0 to +40°C, ±1 min/year for standard TCXO)
- Humidity: Up to 90%, non-condensing

Dry Contact Relay Option **New!**

- Upon loss of lock from NTP source NO/NC dry contact relay inside the clock is energized.