



Rear view

### FEATURES

- Time and date display with 6 - 7" (18cm) digits and 6 - 4" (10.2cm) digits
- Display colors available in **red**, **green**, **amber**, or **blue**
- Syncs to external or internal NTP source for accurate traceable time
- Display time in 12 or 24 hr format – hh:mm:ss
- Display date in dd:MM:yy, MM:dd:yy, or yy:MM:dd
- Adjustable brightness levels
- All international time zones and automatic daylight saving times
- Standard chassis is burnished stainless steel
- Worldwide AC power options

### SPECIFICATIONS

#### Setup and control software

- Supports DHCP/BOOTP for automatic acquisition of network address, nameservers, and time server configuration
- Provides dynamic configuration for networking parameters, time zone/daylight saving time
- Configure clocks through provided WinDiscovery software or TELNET
- WinDiscovery provides easy discovery and configuration of NTP clocks attached to the network without changing PC's network configuration
- Configuration is saved to non-volatile memory
- Encrypted network messages prevent unauthorized tampering of clock configuration

#### Physical

Powder-coated, non-rusting, welded steel chassis

**Size:** 39.4w x 15h x 2.6d in      **Weight:** 25 lbs  
100.4w x 38.1h x 6.7d cm      11.3 kg

#### Connectors

- Ethernet – RJ45
- Optional AC input - IEC connector

#### Power

- Power consumption 15W
- AC power - International 90-264 VAC, 47-63 Hz
  - Supplied with your choice of US, Euro, British or AUS/NZ power cord – others available

#### Operating Temperature and Humidity

- Temperature: 0 to +60°C (0 to +40°C, ±1 min/year for standard TCXO)
- Humidity: Up to 90%, non-condensing