

NTP100-TC NTP Server

The NTP100-TC is an NTP time server that synchronizes to a time code source and converts the signal to Network Time Protocol. It automatically detects the incoming time code source; long-term accuracy is the same as the external source. With loss of time code, the device will revert to an internal oscillator with accuracy of better than 165 msec/day.

Standard Features

- · Compact NTP client / server
- Internal precision TCXO accurate of ± 1 min/year
- Optional OCXO accurate of ± 250ms/year
- NTP output accuracy of ± 2 milliseconds
- 6-digit clock display (red)
- · Adjustable time display brightness

Specifications

TIME CODE INPUTS

 IRIG-B0 (DCLS), IRIG-B1 (AM), IRIG-A0 (DCLS), IRIG-A1 (AM), IRIG-E0 (DCLS), IRIG-E1 (AM), SMPTE 12M, 309M, 24/25/30 fps, 29.97 drop frame

HOLDOVER ACCURACY

- Internal precision TCXO temperature-compensated crystal oscillator provides accuracy of ± 1min/year or < 165 ms/day
- High-stability option with OCXO provides typical stability of 1 ppb/day (± 250ms/year) after 30 days of aging

NETWORK COMPATIBILITY

- Supports NTP, DHCPv4, DHCPv6 for automatic acquisition of network address, name servers, and timeserver configuration
- Telnet/SSH communication
- IPv4/IPv6 compatible
- SNMP with custom MIB



CONFIGURATION

- Configure devices through provided WinDiscovery or SSH
- Configuration is saved to nonvolatile memory and survives power losses
- Authenticated network messages prevent
 unauthorized tampering of clock configuration

CONNECTORS

- RJ45 10/100MB Ethernet
- DC input 2.1mm male jack
- RS-232 9 pin male
- USB for configuration

POWER

- DC input (9-28 VDC)
- Power consumption: < 7.5W
- Includes external 24 VDC wall-mount power supply with locking DC plug (UL and CE listed)

OPERATING PARAMETERS

- Temperature: 0 to 60°C
- Humidity: Up to 90% (non-condensing)
- MTBF: 625,979 hours Calculated using Fixed/Ground Mil HDBK 217F assumptions
- IP Rating: IP30

PHYSICAL

- Size: 6.44 x 4.06 x 1.44 in (16.35 x 10.32 x 3.65 cm)
- Weight: 16 oz (453.6 g)

COMPLIANCE

FCC, ROHS, CE Marked, ANSI



Mount multiple units with the RM4 rack mount

5-YEAR LIMITED PARTS & LABOR WARRANTY MADE IN THE USA