

The **NTDS4626-3AL** Digital Clock syncs to any NTP (Network Time Protocol) source for accurate and traceable time. The unit configures to time zone and Daylight Saving Time parameters and can be powered via PoE. WinDiscovery software is included.



## Standard Features

- 4 in (10.2 cm) 6-digit LED display on top row; 2.3 inch (5.8 cm) 6-digits on bottom row with 2.3 in (5.8 cm) 3-digit alphanumeric display
- LED available in red, green, blue or amber
- Syncs to any NTP or SNTP source for accurate and traceable time
- Retains time and date during loss of power and/or reference using a battery backed real-time clock (RTC) chip and maintenance-free rechargeable battery
- Configures to time zone and Daylight Saving Time
- WinDiscovery software utility included for easy configuration of clocks and generators when a network
- Fully configurable network settings, including DHCP / STATIC IP
- Configuration is saved to non-volatile memory and survives power losses
- Password protection prevents unauthorized tampering
- Display time in 12- or 24-hr format - hh:mm:ss
- Display date - mm:dd:yy, dd:mm:yy or yy:mm:dd
- Dual time display
- Alpha-numeric characters available in : English, Spanish, French, German, Russian, Italian, Portuguese, Slovenian, and Dutch
- Wall mount bracket
- Adjustable brightness levels with scheduled dimming
- Visibility: 200 feet (60 meters)

## Options

- Flush-mount case
- Stainless steel case
- Ceiling mount bracket

Pair with the **RC1000** or **RC600** to add count-up and count-down timer control functionality



## Specifications

LED available in red, green, blue or amber

### CONNECTORS

- Ethernet RJ45
- IEC AC Power
- DC input
- USB for configuration

### POWER

- Choice of IEC AC, PoE (IEEE802.3af), or DC (24 VDC)
- International IEC AC 90-240v, 50/60 Hz
- Power consumption < 15W

### OPERATING PARAMETERS

- Temperature: 0 to 60°C
- Humidity: Up to 90% (non-condensing)
- Storage Temperature: -40° to 185° F (-40° to 85°C)
- Storage Humidity: Up to 90% (non-condensing @ 25°C)

### PHYSICAL

- Black powder-coated steel chassis
- IP Rating: IP40
- Size: 25.5w x 10.4h x 2.3d in (64.8w x 26.4h x 5.8d cm)
- Weight: 11 lbs (5.0 kg)

### MTBF

- 86,700 - 100,000 hrs
- All calculated using Fixed/Ground Mil HDBK 217F assumption

### COMPLIANCE

- FCC, ROHS, CE Marked, ANSI



**5-YEAR LIMITED PARTS & LABOR WARRANTY**    **MADE IN THE USA**

US/CAN: (800) 940-2248    INTL: +1 (636) 724-3666    sales@masterclock.com

[Masterclock.com](http://Masterclock.com)