

The **TCDS86** Digital Clock syncs to IRIG-B, SMPTE and EBU time codes for accurate and traceable time. The unit configures to time zone and Daylight Saving Time parameters. WinDiscovery software is included.

**Masterclock®** 



LED available in red, green, blue or amber



TIME CODE

# **Standard Features**

- 7 in (18 cm) 6-digit LED display
- LED available in red, green, blue or amber
- Reads IRIG-B, SMPTE 12M, 309M, 24/25/30 fps, 29.97 drop frame
- Retains time and date during loss of power and/or reference using a battery backed real-time clock (RTC) chip and maintenance-free rechargeable battery
- Configures to time zone and Daylight Saving Time
- WinDiscovery software utility included for easy configuration through USB
- Configuration is saved to non-volatile memory and survives power losses
- · Password protection prevents unauthorized tampering
- Display time in 12- or 24-hr format hh:mm:ss
- Display date mm:dd:yy, dd:mm:yy or yy:mm:dd
- · Configurable to alternate showing date and time
- PM indicator
- · Wall mount bracket
- · Adjustable brightness levels with scheduled dimming
- Visibility: 350 feet (100 meters)

### **Options**

- Tilt-wall bracket
- Stainless steel case

# Pair with the RC1000 or RC600 to add count-up and count-down timer control functionality





# **Specifications**

#### **CONNECTORS**

- BNC female
- 3-pin terminal block
- USB for configuration
- 2.1 mm female DC power plug
- IEC C5 A/C Power

#### **POWER**

- Choice of IEC AC or DC (24 VDC)
- International IEC AC 90-240v, 50/60 Hz
- Power consumption < 15W

#### **OPERATING PARAMETERS**

- Temperature: 0° to 60°C
- Humidity: Up to 90% (non-condensing)
- Storage Temperature: -40° to 185° F (-40° to 85°C)
- Storage Humidity: Up to 90% (non-condensing @ 25°C)

#### **PHYSICAL**

- Black metal chassis
- IP Rating: IP40
- Size: 37.3w x 9.75h x 2.63d in (94.7w x 24.8h x 6.68d cm)
- Weight: 12.0 lbs (5.4 kg)

## MTBF

86,700 - 100,000 hrs
All calculated using Fixed/Ground Mil HDBK 217F assumption

#### **COMPLIANCE**

FCC, ROHS, CE Marked, ANSI

5-YEAR LIMITED PARTS & LABOR WARRANTY MADE IN THE USA