



The optional **RC600** (right) is a remote control that adds both count-down and count-up timer control features to our NTDS and TCDS clocks.



The **TCDS49** digital clock syncs to IRIG-B, SMPTE and EBU time codes for accurate traceable time. Each unit configures to time zone and daylight savings time parameters. WinDiscovery software is included.

Features

- 4-in (10.2 cm) 9-digit LED display available in red or blue
- Reads IRIG-B, SMPTE 12M, 309M, 24/25/30 fps, 29.97 drop frame
- Retains time and date during loss of power and/or reference using a battery backed real-time clock (RTC) chip and maintenance-free rechargeable battery
- Configures to time zone and daylight saving time parameters
- WinDiscovery software utility included - provides easy configuration of clocks
- Configuration is saved to non-volatile memory and survives power losses
- Password protection prevents unauthorized clock configuration tampering
- Display time in 12- or 24-hr format - hh:mm:ss with three digit Day of Year
- Display date - mm:dd:yy, dd:mm:yy or yy:mm:dd - configurable
- Configurable to alternate showing date and time automatically
- Adjustable brightness levels with auto-dimming option
- Visibility: 200 feet (60 meters)
- Wall-mount bracket
- Dry contact relay option
- PM Indicator

Options

- Tilt-wall bracket

Specifications

Connectors

- BNC female
- 3-pin terminal block
- USB for configuration
- DC input - 2.1 mm female
- IEC Std A/C Power

Power

- Choice of - IEC AC or DC (24 VDC)
- International IEC AC 90-240v, 50/60 Hz
- Power consumption < 15W

Operating Parameters

- Temperature: 0 to 60°C
- Humidity: Up to 90% (non-condensing)

Physical

- Black powder-coated steel chassis
Size: 42w x 6.5h x 2.3d in (106.7w x 16.5h x 5.8d cm)
Weight: 9.0 lbs (4.0 kg)

Compliance

- FCC, ROHS, CE Marked, ANSI