

## FEATURES

- Syncs to SMPTE, EBU and IRIG-B time codes
- Complete flexibility in daylight saving time and time zone configurations
- Front indicator light provides synchronization status
- Microprocessor-controlled stepper motor with sweeping second hand for quiet operation
- Battery-backed real time clock chip in case of loss of synchronization or power



## SPECIFICATIONS

### Time Code Inputs

- > SMPTE (30/25/25 fps - non-drop frame only) to Leitch Date Encoding Standard
- > IRIG-B pulse width coded (unmodulated) DC, IEEE 1344 standard
- > IRIG-B(1) 1 kHz Amplitude Modulated, IEEE 1344 standard

### Holdover Accuracy

- > With loss of power, device reverts to an internal battery-backed real-time clock chip with accuracy of  $\pm 1$ min/year or  $< 165$ ms per day

### Connectors

- > BNC female
- > Optional twisted pair to BNC adapter available
- > IEC 320 AC input
- > USB port for configuration

### Options

- > 12/24-hour face
- > 24-hour face
- > Face plate illumination
- > Stainless steel chassis

### Physical

- > Size: 12.5 in (31.8 cm) w, 2.5 in (6.35 cm) h
- > Weight: 2.52 lb (1.14 kg)
- > Black powder-coated steel chassis
- > Polycarbonate lens
- > Wall mount bracket provided

### Configuration

- > Configure devices through supplied WinDiscovery software
- > Configuration is saved to nonvolatile memory and survives power losses

### Power

- > 90-265 VAC 50/60 Hz
- > IEC AC power connector and cord

### Operating Parameters

- > Temperature: 0 to 60°C
- > Humidity: Up to 90% (non-condensing at +25°C)

### Compliance

- > FCC, CE Marked, ROHS, ANSI

**MASTERCLOCK, INC.**

**5-YEAR LIMITED PARTS & LABOR WARRANTY**

**MADE IN THE USA**

phone (USA and Canada):  
1-800-940-2248

phone (international):  
+1-636-724-3666

email:  
sales@masterclock.com

online:  
www.masterclock.com